



# STRUCTURAL PERMANENT BONDING TAPES

**Fix**tech structural FAT tapes are structural bonding tapes for a permanent adhesion between components. Uses are for bonding control panels, name plates on boats, panel fastening, nylon sliding runners for push outs in caravans and motor-homes and many other structural bonding applications and it can be used alongside Fixtech adhesive sealants range.



**FAT100865**

- High strength structural acrylic adhesive tape. FAT10 will structurally bond to all non porous surfaces such as gelcoat, most plastics (including nylon), most metals and glass without any other method of fastening.
- Size **10mm x 0.8mm x 65m roll**
- Fully structural and must be used as an adhesive between two substrates. Under pressure the adhesive tape required 3 days to fully gain strength



**FAT300865**

- High strength structural acrylic adhesive tape. FAT30 will structurally bond to all non porous surfaces such as gelcoat, most plastics (including nylon), most metals and glass without any other method of fastening.
- Size **30mm x 0.8mm x 65m roll**
- Fully structural and must be used as an adhesive between two substrates. Under pressure the adhesive tape required 3 days to fully gain strength

Base	Acrylic adhesive on Acrylic Foam
Curing system	Pressure
Consistency	Tap format double sided adhesive foam
Colour	Grey
Thickness	0.8mm and 1.2mm (On request)
Maximum Width	800mm (Request for different widths)
External covering	Red PE
Density	0.8g/mL
Tensile Strength	0.69N/mm <sup>2</sup>
Shear Strength	0.64N/mm <sup>2</sup> After 72 hours at room temperature 23°C
Peel Strength	1.2 N/mm
Durability against ageing	Excellent
Temperature resistance	-40°C to 90°C typical up to 150°C short term

STRUCTURAL PERMANENT BONDING TAPES





# Glazing Dam Tapes

## GLAZING TAPES FOR WINDOW INSTALLATION



**FGT0904L15DSBK**

UV resistant weatherproof double sided adhesive glazing tape. High density (Hard to compress and bend),

9mm wide, 4.0mm high 15m on the roll. Designed to keep glass a constant distance from substrate no matter what the force applied to it through the glass during installation.



**FGT0905L15DSBK**

No. 1 UV resistant weatherproof double sided adhesive glazing tape. Medium density, (can compress with point load, can bend and is best for use around window openings as a dam tape)

9mm wide, 5mm high 15m on the roll. Designed to keep glass a constant distance from substrate and is ideal as a finished seal internally.



**FGT1203L25DSBK**

No. 1 UV resistant weatherproof double sided adhesive glazing tape. Medium density, (can compress with point load, can bend and is best for use around window openings as a dam tape)

12mm wide, 3mm high 25m on the roll. Designed to keep glass a constant distance from substrate and is ideal as a finished seal internally.

